



FT series FT10II

Two-way Loudspeaker System

The FT10 II is a 10" two-way full range speaker. Unit configuration: 1x10" high efficiency mid-bass unit, 1x1" exit throat 25mm mylar diaphragm HF driver with 90°×50° rotatable horn. The cabinet is made of MDF with water-based environmental protection paint.

FT10 II 是一款10"两分音全音域音箱。单元配置: 1只10"高效率低音单元,1只1"喉口25芯高分子聚酯膜高音驱动器配置 90°×50° 可旋转号角。箱体采用高密度复合板,水性环保喷涂制作。

FEATURES

- High quality MDF housing
- Light weight, easy handling and fixed installation
- Multi-hanging points and support, easy and quick operation
- Applications: full range reinforcement, speech and conference halls, background music, classrooms


产品特征


- ●高强度复合板箱体
- 重量轻便于搬运和固定安装
- ●多吊挂点与支撑配合,操作简易快捷

适用范围

- 用于全音域扩声、语言扩声会议系统
- ●背景音乐重放、学校教室

CONFIGURATION





MODEL

FREQUENCY RESPONSE(-3dB) FREQUENCY RESPONSE(-10dB) DRIVERS

RATED POWER
SENSITIVITY
MAXIMUM SPL
IMPEDANCE
DISPERSION(-6dB)
CROSSOVER FREQUENCIES

PACKAGE SIZE
NET WEIGHT
GROSS WEIGHT

INPUT CONNECTORS

FT10 $\scriptstyle\rm II$

50Hz-18kHz

45Hz-20kHz

 1×10 "(250mm)/2" voice coil LF

 $1\times1"$ (25mm)/ 1"voice coil HF

150W RMS,600W peak

95dB 1watt/1 metre

117 dB continuous,123 dB peak

8 ohms nominal

90°×50°

2.2 kHz passive

2×Speakon NL4

440mm×400mm×585mm

13 kg/pc

15 kg/pc

